

206.25 x 42.9 mm bar light

LS-BAR-0108 series · Bar lights · 4 models

25 x 42.9 mm bar light. Lit area 152.4 x 31.7 mm. Connection: Flying Leads. Available in 198 configurations (color, driver included, driver location, driver nomenclature); choose one below and request a quote. Rendered illustration: the actual product may differ in appearance.



Common specifications

Active Width (mm)	31.7
Cable Length (mm)	2
Collimated	Not Collimated
Compliances	CE, IEC 62471, RoHS
Connector Type	Flying Leads
Connectorized At Light	Hardwired
Daisy Chain	No
Direct Connect	No
Height (mm)	24
IP Rating	IP69K
Maximum Duty Cycle (%)	100
Maximum Operating Temperature (C)	60
Maximum Operating Temperature (F)	140
Minimum Operating Temperature (F)	32
Mounting Method	Tapped Holes
Polarized	Not Polarized
Voltage	24 VDC
Width (mm)	42.9

Models

Model	Active Length (mm)	Length (mm)	Product Weight (Kg)	Product Weight (Lbs)
LS-BAR-0108-L1	152.4	206.25	0.42	0.92
LS-BAR-0108-L2	304.8	358.65	0.66	1.45
LS-BAR-0108-L3	457.2	511.05	0.9	1.99
LS-BAR-0108-L4	609.6	663.45	1.14	2.52

Product views

