

308 x 52.4 mm bar light

LS-BAR-0139 series · Bar lights · 1 model

308 x 52.4 mm bar light. Lit area 292.4 x 31.4 mm. Connection: 5 Pin M12 Male A-Coded. Available in 81 configurations (color, daisy chain, direct connect, lens angle); choose one below and request a quote. Rendered illustration: the actual product may differ in appearance.



Options

Color	470nm Blue, 530nm Green, 625nm Red, 850nm Infrared, WHITE
Daisy Chain	No, Yes
Direct Connect	Yes, No
Lens Angle	10 Degree, 10 x 50 Degree, 25 Degree
Mounting Method	Tapped Holes, Through Holes
Operation Modes	Constant On, Constant On – Dimmable, Overcurrent Strobe – Dimmable, Strobe, Strobe – Dimmable, Constant On, Constant On – Dimmable, Overcurrent Strobe, Strobe, Strobe – Dimmable
Polarized	Not Polarized, Polarized

Order by the full LS number of the chosen configuration; we confirm it with your quote.

Common specifications

Active Length (mm)	292.4
Active Width (mm)	31.4
Collimated	Not Collimated
Compliances	CE, IEC 62471, RoHS
Connector Type	5 Pin M12 Male A-Coded
Connectorized At Light	Connectorized
Driver Included	Included
Driver Location	Internal
Driver Nomenclature	SVL Multi-Drive
Height (mm)	47.2

Housing Material	Aluminum
IP Rating	IP65
Intensity Adjustment Type	Analog Voltage, SmartVisionLink
Length (mm)	308
Maximum Constant On Current (mA)	750
Maximum Current (Overcurrent Strobe) (mA)	4500
Maximum Duty Cycle (%)	100
Maximum Input Power Constant On (W)	18
Maximum Input Power Overcurrent Strobe (W)	108
Maximum Operating Temperature (C)	40
Maximum Operating Temperature (F)	104
Maximum Overcurrent Strobe Duration (ms)	50
Maximum Overcurrent Strobe Duty Cycle (%)	10
Maximum Overcurrent Strobe Frequency (Hz)	4000
Maximum Overcurrent Strobe Latency (us)	6
Maximum Storage Temperature (C)	70
Maximum Storage Temperature (F)	158
Maximum Strobe Current (mA)	750
Maximum Strobe Duration (ms)	No Limit
Maximum Strobe Duty Cycle (%)	100
Maximum Strobe Frequency (Hz)	4000
Maximum Strobe Input Power (W)	18
Maximum Strobe Latency (us)	10
Minimum Operating Temperature (C)	-10
Minimum Operating Temperature (F)	14
Minimum Overcurrent Strobe Duration (us)	30
Minimum Storage Temperature (C)	-20
Minimum Storage Temperature (F)	-4
Minimum Strobe Duration (us)	30
NPN Trigger Current (mA)	12
NPN Trigger Voltage (V)	< 1 VDC
PNP Trigger Current (mA)	13.4
PNP Trigger Voltage (V)	3.3-24 VDC
Product Weight (Kg)	0.9
Product Weight (Lbs)	1.98
Strobe Trigger Input	NPN Trigger, PNP Trigger
Voltage	24 VDC
Width (mm)	52.4

Models