


# 82.8 x 50.2 mm backlight

LS-BKL-0032 series · Backlights · 1 model

82.8 x 50.2 mm backlight.  
 Colour: WHITE. Lit area 77.22 x 24.6 mm.  
 Connection: Flying Leads.  
 Available in 2 configurations (driver included, driver location, driver nomenclature, intensity adjustment type); choose one below and request a quote.  
 Rendered illustration: the actual product may differ in appearance.



## Options

|                                     |                                                  |
|-------------------------------------|--------------------------------------------------|
| Driver Included                     | No Driver Required, Included                     |
| Driver Location                     | No Driver, In Line                               |
| Driver Nomenclature                 | 24V, iCS2 - IC                                   |
| Maximum Constant On Current (mA)    | 407, 543                                         |
| Maximum Input Power Constant On (W) | 9.8, 13                                          |
| Operation Modes                     | Constant On, Constant On, Constant On - Dimmable |

Order by the full LS number of the chosen configuration; we confirm it with your quote.

## Common specifications

|                        |                     |
|------------------------|---------------------|
| Active Length (mm)     | 77.22               |
| Active Width (mm)      | 24.6                |
| Cable Length (mm)      | 2000                |
| Collimated             | Not Collimated      |
| Color                  | WHITE               |
| Compliances            | CE, IEC 62471, RoHS |
| Connector Type         | Flying Leads        |
| Connectorized At Light | Hardwired           |
| Daisy Chain            | No                  |

|                                   |                  |
|-----------------------------------|------------------|
| Direct Connect                    | No               |
| Height (mm)                       | 90.7             |
| Housing Material                  | Aluminum         |
| Length (mm)                       | 82.8             |
| Maximum Duty Cycle (%)            | 100              |
| Maximum Operating Temperature (C) | 60               |
| Maximum Operating Temperature (F) | 140              |
| Minimum Operating Temperature (F) | 32               |
| Mounting Method                   | T-Slot Channel   |
| Polarized                         | Not Polarized    |
| Product Weight (Kg)               | 0.48             |
| Product Weight (Lbs)              | 1.06             |
| Strobe Trigger Input              | Constant On Only |
| Voltage                           | 24 VDC           |
| Width (mm)                        | 50.2             |
| Intensity Adjustment Type         | Analog Voltage   |

## Models

Model

LS-BKL-0032

## Product views

