


159 x 50.2 mm backlight

LS-BKL-0033 series · Backlights · 1 model

159 x 50.2 mm backlight.
 Colour: WHITE. Lit area 152.4 x 24.6 mm.
 Connection: Flying Leads. Available in 2 configurations (driver included, driver location, driver nomenclature, intensity adjustment type); choose one below and request a quote.
 Rendered illustration: the actual product may differ in appearance.



Options

Driver Included	No Driver Required, Included
Driver Location	No Driver, In Line
Driver Nomenclature	24V, iCS2 - IC
Maximum Constant On Current (mA)	782, 1043
Maximum Input Power Constant On (W)	18.8, 25
Operation Modes	Constant On, Constant On, Constant On - Dimmable

Order by the full LS number of the chosen configuration; we confirm it with your quote.

Common specifications

Active Length (mm)	152.4
Active Width (mm)	24.6
Cable Length (mm)	2000
Collimated	Not Collimated
Color	WHITE
Compliances	CE, IEC 62471, RoHS
Connector Type	Flying Leads
Connectorized At Light	Hardwired
Daisy Chain	No

Direct Connect	No
Height (mm)	90.7
Housing Material	Aluminum
Length (mm)	159
Maximum Duty Cycle (%)	100
Maximum Operating Temperature (C)	60
Maximum Operating Temperature (F)	140
Minimum Operating Temperature (F)	32
Mounting Method	T-Slot Channel
Polarized	Not Polarized
Product Weight (Kg)	0.77
Product Weight (Lbs)	1.7
Strobe Trigger Input	Constant On Only
Voltage	24 VDC
Width (mm)	50.2
Intensity Adjustment Type	Analog Voltage

Models

Model
LS-BKL-0033

Product views

