Backlight, 240.3 x 25.4 mm lit area

LS-BKL-0057 series · Backlights · 1 model

LED backlight for silhouette imaging: gauging, presence and edge inspection, with the part between the light and the camera. Lit area 240.3 x 25.4 mm; 24 VDC supply; connection: flying leads. Choose colour, driver included, driver location, intensity control, operating modes below (16 configurations) and request a quote. Rendered illustration: the actual product may differ in appearance.

Options

Colour	470nm Blue, 520nm Green, 660nm Red, WHITE
Driver included	No Driver Required, Included
Driver location	No Driver, In Line
Operating modes	Constant On, Constant On, Constant On – Dimmable, Overcurrent Strobe, Overcurrent Strobe - Dimmable, Constant On, Constant On – Dimmable
Strobe trigger input	Constant On Only, PNP Trigger
Version	Standard, Version 1, Version 2

Order by the full LS number of the chosen configuration; we confirm it with your quote.

Common specifications

Lit length (mm)	240.3
Lit width (mm)	25.4
Length (mm)	250.4
Width (mm)	33.8
Height (mm)	30

Voltage	24 VDC
Connector	Flying Leads
Connection at light	Hardwired
Cable length (mm)	2000
Operating temperature	up to 60 °C
IP rating	IP50
Housing	Aluminum
Mounting	T-Slot Channel
Collimated	Not Collimated
Daisy chain	No
Diffused	Not Diffused
Direct connect	No
Driver nomenclature	24V / iCS2 - IC (by configuration)
Maximum constant on current (ma)	197 / 295 (by configuration)
Maximum current (overcurrent strobe) (ma)	8000 (by configuration)
Maximum duty cycle (%)	100
Maximum input power constant on (w)	4.7 / 7.1 (by configuration)
Maximum input power overcurrent strobe (w)	125 (by configuration)
Maximum overcurrent strobe frequency (hz)	2000 (by configuration)
Maximum overcurrent strobe latency (us)	60 (by configuration)
Minimum overcurrent strobe duration (us)	30 (by configuration)
NPN trigger voltage (v)	< 1 VDC (by configuration)
PNP trigger current (ma)	5 (by configuration)
PNP trigger voltage (v)	2.5-30 VDC (by configuration)
Polarized	Not Polarized
Compliance	CE, IEC 62471, RoHS
Intensity control	Analog Voltage

Models

Model
LS-BKL-0057

Product views