# 1063.24 x 33.8 mm backlight

LS-BKL-0089 series · Backlights · 1 model

1063.24 x 33.8 mm backlight. Lit area 1053.08 x 25.4 mm. Connection: Flying Leads. Available in 20 configurations (color, driver included, driver location, driver nomenclature); choose one below and request a quote. Rendered illustration: the actual product may differ in appearance.



## Options

| | |
|---|---|
| Color | 470nm Blue, 520nm Green, 660nm Red, WHITE |
| Driver Included | No Driver Required, Included |
| Driver Location | No Driver, In Line |
| Driver Nomenclature | 24V, iCS4 - I4, iCS2 - IC |
| Maximum Constant On Current (mA) | 837, 1255 |
| Maximum Input Power Constant On (W) | 20.1, 30.1 |
| Maximum Input Power Overcurrent Strobe (W) | 125, 150 |
| Maximum Overcurrent Strobe Latency (us) | 60, 20 |
| Operation Modes | Constant On, Constant On, Constant On – Dimmable, Overcurrent Strobe, Overcurrent Strobe - Dimmable, Constant On, Constant On – Dimmable |
| Strobe Trigger Input | Constant On Only, PNP Trigger |

Order by the full LS number of the chosen configuration; we confirm it with your quote.

## Common specifications

| | |
|---|---|
| Active Length (mm) | 1053.08 |
| Active Width (mm) | 25.4 |
| Cable Length (mm) | 2000 |
| Collimated | Not Collimated |
| Compliances | CE, IEC 62471, RoHS |

| | |
|---|---|
| Connector Type | Flying Leads |
| Connectorized At Light | Hardwired |
| Daisy Chain | No |
| Direct Connect | No |
| Height (mm) | 30 |
| Housing Material | Aluminum |
| IP Rating | IP50 |
| Length (mm) | 1063.24 |
| Maximum Duty Cycle (%) | 100 |
| Maximum Operating Temperature (C) | 60 |
| Maximum Operating Temperature (F) | 140 |
| Minimum Operating Temperature (F) | 32 |
| Mounting Method | T-Slot Channel |
| Polarized | Not Polarized |
| Product Weight (Kg) | 1.18 |
| Product Weight (Lbs) | 2.61 |
| Voltage | 24 VDC |
| Width (mm) | 33.8 |
| Intensity Adjustment Type | Analog Voltage |
| Maximum Current (Overcurrent Strobe) (mA) | 8000 |
| Maximum Overcurrent Strobe Frequency (Hz) | 2000 |
| Minimum Overcurrent Strobe Duration (us) | 30 |
| NPN Trigger Voltage (V) | < 1 VDC |
| PNP Trigger Current (mA) | 5 |
| PNP Trigger Voltage (V) | 2.5-30 VDC |

## Models

| Model |
|---|
| LS-BKL-0089 |

## Product views