

# Backlight, 418.1 x 25.4 mm lit area

LS-BKL-0206 series · Backlights · 1 model

LED  
backlight  
for  
silhouette  
imaging:  
gauging,  
presence  
and edge  
inspection,  
with the  
part  
between  
the light  
and the  
camera. Lit  
area 418.1 x  
25.4 mm; 24  
VDC supply;  
connection:  
flying leads.  
Rendered  
illustration:  
the actual  
product  
may differ in  
appearance.



## Common specifications

|                       |                |
|-----------------------|----------------|
| Colour                | WHITE          |
| Lit length (mm)       | 418.1          |
| Lit width (mm)        | 25.4           |
| Length (mm)           | 428.2          |
| Width (mm)            | 33.8           |
| Height (mm)           | 30             |
| Voltage               | 24 VDC         |
| Connector             | Flying Leads   |
| Connection at light   | Hardwired      |
| Cable length (mm)     | 2000           |
| Driver included       | Included       |
| Driver location       | In Line        |
| Intensity control     | Analog Voltage |
| Operating modes       | Constant On    |
| Strobe trigger input  | PNP Trigger    |
| Operating temperature | up to 60 °C    |
| IP rating             | IP50           |
| Housing               | Aluminum       |
| Mounting              | T-Slot Channel |

