Dome light, 25.5 mm

LS-DOM-0024 series · Dome lights · 1 model

Dome light for diffuse, cloudy-day illumination of curved, shiny and reflective parts; the camera looks through the viewport. Lit area 1076 x 25.5 mm; 24 VDC supply; connection: flying leads. Choose colour, driver included, driver location, intensity control, operating modes below (16 configurations) and request a quote. Rendered illustration: the actual product may differ in appearance.

Options

Colour	455nm Blue, 470nm Blue, 530nm Green, 590nm Amber, 625nm Red, 850nm Infrared, 940nm Infrared, WHITE
Driver included	No Driver Required, Included
Driver location	No Driver, In Line
Operating modes	Constant On, Constant On, Constant On – Dimmable, Overcurrent Strobe, Overcurrent Strobe - Dimmable
Strobe trigger input	Constant On Only, PNP Trigger

Order by the full LS number of the chosen configuration; we confirm it with your quote.

Common specifications

Lit length (mm)	1076
Lit width (mm)	25.5
Length (mm)	1084
Width (mm)	77.9
Height (mm)	40.7
Voltage	24 VDC
Connector	Flying Leads

Connection at light	Hardwired
Cable length (mm)	2000
Operating temperature	up to 60 °C
IP rating	IP67
Housing	Aluminum
Mounting	Tapped Holes
Collimated	Not Collimated
Daisy chain	No
Diffused	Not Diffused
Direct connect	No
Driver nomenclature	24V / iCS4 - I4 (by configuration)
Maximum constant on current (ma)	2542 / 2966 (by configuration)
Maximum current (overcurrent strobe) (ma)	8000 (by configuration)
Maximum duty cycle (%)	100
Maximum input power constant on (w)	61 / 71.2 (by configuration)
Maximum input power overcurrent strobe (w)	150 (by configuration)
Maximum overcurrent strobe frequency (hz)	2000 (by configuration)
Maximum overcurrent strobe latency (us)	20 (by configuration)
NPN trigger voltage (v)	< 1 VDC (by configuration)
PNP trigger current (ma)	5 (by configuration)
PNP trigger voltage (v)	2.5-30 VDC (by configuration)
Polarized	Not Polarized
Compliance	CE, IEC 62471, RoHS
Intensity control	Analog Voltage

Models

Model
LS-DOM-0024

Product views