

Classic bar lights

LS-LLDS-C series · Bar lights · 49 models

One-piece aluminum alloy body for good heat dissipation
Multiple mounting options: both ends and back

Features

- One-piece aluminum alloy body for good heat dissipation
- Multiple mounting options: both ends and back
- High-quality LEDs with high brightness



Common specifications

Connector type	SMR-03V-B
Cable length	500 mm
Temperature	Working temperature: 0 °C to 40 °C (32 °F to 104 °F); Storage temperature: -20 °C to 60 °C (-4 °F to 140 °F)
Humidity	20% to 85% RH (non-condensing)
Diffuse plate included	Included

Models

Model	Color	Color temperature	Power	LED rows	Dimension	Emitting area length	Wavelength
LS-LLDS-57-38-W	White	6000~7000K	2.4 W	6	57 mm × 38 mm × 27 mm	45 mm × 32 mm	-
LS-LLDS-57-18-W	White	6000~7000K	0.7 W	2	57 mm × 18 mm × 27 mm	45 mm × 12 mm	-
LS-LLDS-57-28-W	White	6000~7000K	1.4 W	4	57 mm × 28 mm × 27 mm	45 mm × 22 mm	-
LS-LLDS-102-38-W	White	6000~7000K	2.9W	6	102 mm × 38 mm × 27 mm	90 mm × 32 mm	-
LS-LLDS-102-18-W	White	6000~7000K	2.6 W	2	102 mm × 18 mm × 27 mm	90 mm × 12 mm	-
LS-LLDS-102-28-W	White	6000~7000K	2.9 W	4	102 mm × 28 mm × 27 mm	90 mm × 22 mm	-
LS-LLDS-147-18-W	White	6000~7000K	2.2 W	2	147 mm × 18 mm × 27 mm	135 mm × 12 mm	-
LS-LLDS-147-38-W	White	6000~7000K	6.5W	6	147 mm × 38 mm × 27 mm	135 mm × 32 mm	-

LS-LLDS-147-28-W	White	6000~7000K	4.3 W	4	147 mm × 28 mm × 27 mm	135 mm × 22 mm	-
LS-LLDS-192-18-W	White	6000~7000K	2.9 W	2	192 mm × 18 mm × 27 mm	180 mm × 12 mm	-
LS-LLDS-192-38-W	White	6000~7000K	9.8 W	6	192 mm × 38 mm × 27 mm	180 mm × 32 mm	-
LS-LLDS-192-28-W	White	6000~7000K	5.8 W	4	192 mm × 28 mm × 27 mm	180 mm × 22 mm	-
LS-LLDS-237-18-W	White	6000~7000K	3.6 W	2	237 mm × 18 mm × 27 mm	225 mm × 12 mm	-
LS-LLDS-237-38-B	Blue	-	9.8 W	6	237 mm × 38 mm × 27 mm	225 mm × 32 mm	465 nm
LS-LLDS-237-28-W	White	6000~7000K	7.2 W	4	237 mm × 28 mm × 27 mm	225 mm × 22 mm	-
LS-LLDS-237-38-W	White	6000~7000K	10.8 W	6	237 mm × 38 mm × 27 mm	225 mm × 32 mm	-
LS-LLDS-237-38-R	Red	-	12.2 W	6	237 mm × 38 mm × 27 mm	225 mm × 32 mm	625 nm
LS-LLDS-282-28-W	White	6000~7000K	8.6 W	4	282 mm × 28 mm × 27 mm	270 mm × 22 mm	-
LS-LLDS-282-18-W	White	6000~7000K	4.3 W	2	282 mm × 18 mm × 27 mm	270 mm × 12 mm	-
LS-LLDS-282-38-W	White	6000~7000K	14.7 W	6	282 mm × 38 mm × 27 mm	270 mm × 32 mm	-
LS-LLDS-327-28-W	White	6000~7000K	10 W	4	327 mm × 28 mm × 27 mm	315 mm × 22 mm	-
LS-LLDS-327-18-W	White	6000~7000K	5 W	2	327 mm × 18 mm × 27 mm	315 mm × 12 mm	-
LS-LLDS-327-38-W	White	6000~7000K	15.1 W	6	327 mm × 38 mm × 27 mm	315 mm × 32 mm	-
LS-LLDS-372-18-W	White	6000~7000K	5.8 W	2	372 mm × 18 mm × 27 mm	360 mm × 12 mm	-
LS-LLDS-372-28-W	White	6000~7000K	11.5 W	4	372 mm × 28 mm × 27 mm	360 mm × 22 mm	-
LS-LLDS-372-38-W	White	6000~7000K	17.6 W	6	372 mm × 38 mm × 27 mm	360 mm × 32 mm	-
LS-LLDS-417-18-W	White	6000~7000K	6.5 W	2	417 mm × 18 mm × 27 mm	405 mm × 12 mm	-
LS-LLDS-417-28-W	White	6000~7000K	13 W	4	417 mm × 28 mm × 27 mm	405 mm × 22 mm	-
LS-LLDS-417-38-W	White	6000~7000K	22W	6	417 mm × 38 mm × 27 mm	405 mm × 32 mm	-
LS-LLDS-462-18-W	White	6000~7000K	7.2 W	2	462 mm × 18 mm × 27 mm	450 mm × 12 mm	-
LS-LLDS-462-28-W	White	6000~7000K	14.4 W	4	462 mm × 28 mm × 27 mm	450 mm × 22 mm	-
LS-LLDS-462-38-W	White	6000~7000K	24.5 W	6	462 mm × 38 mm × 27 mm	450 mm × 32 mm	-
LS-LLDS-507-18-W	White	6000~7000K	7.9 W	2	507 mm × 18 mm × 27 mm	495 mm × 12 mm	-
LS-LLDS-507-28-W	White	6000~7000K	15.8W	4	507 mm × 28 mm × 27 mm	495 mm × 22 mm	-

Product views

