

Line scan light, 50.8–762 mm lit length

LS-LSC-0019 series · Line scan lights · 1 model

High-intensity line light for line scan cameras on moving webs and conveyors. 24 VDC supply; connection: flying leads. Choose colour, lit length, length, driver included, driver location below (264 configurations) and request a quote. Rendered illustration: the actual product may differ in appearance.



Options

Colour	455nm Blue, 660nm Red, 730nm Infrared, 850nm Infrared, 940nm Infrared, WHITE
Lit length (mm)	50.8, 101.6, 152.4, 203.2, 254, 304.8, 355.6, 406.4, 457.2, 508, 558.8, 609.6, 660.4, 711.2, 762
Length (mm)	72.9, 123.7, 174.5, 225.3, 276.1, 326.9, 377.7, 428.5, 479.3, 530.1, 580.9, 631.7, 682.5, 733.3, 784.1
Driver included	No Driver Required, Included
Driver location	No Driver, In Line
Intensity control	Not listed, Analog Voltage
Operating modes	Constant On, Constant On, Constant On – Dimmable, Overcurrent Strobe, Overcurrent Strobe – Dimmable, Constant On, Constant On – Dimmable
Strobe trigger input	Not Dimmable, Analog Voltage
Minimum overcurrent strobe duration (us)	Not listed, 30
Version	Standard, Version 1, Version 2

Order by the full LS number of the chosen configuration; we confirm it with your quote.

Common specifications

Lit width (mm)	14.7
Width (mm)	20
Height (mm)	20.1
Voltage	24 VDC
Connector	Flying Leads
Connection at light	Hardwired
Cable length (mm)	2000
Operating temperature	up to 60 °C
Housing	Aluminum
Mounting	T-Slot Channel
Collimated	Not Collimated
Daisy chain	No
Diffused	Not Diffused
Direct connect	No
Maximum constant on current (ma)	175 to 1907 (by configuration)
Maximum current (overcurrent strobe) (ma)	8000 (by configuration)
Maximum duty cycle (%)	100
Maximum input power constant on (w)	4.2 to 45.8 (by configuration)
Maximum input power overcurrent strobe (w)	125 / 150 (by configuration)
Maximum overcurrent strobe frequency (hz)	2000 (by configuration)
Maximum overcurrent strobe latency (us)	20 / 60 (by configuration)
NPN trigger voltage (v)	< 1 VDC (by configuration)
PNP trigger current (ma)	5 (by configuration)
PNP trigger voltage (v)	2.5-30 VDC (by configuration)
Polarized	Not Polarized
Compliance	CE, IEC 62471, RoHS

Models

Model

LS-LSC-0019

Product views

