

Line scan light series, 62.6 mm high, 5 Pin M12 Male A-Coded

LS-LSC-S06 series · Line scan lights · 4 models

Lit area 1196 x 21.8 mm; 24 VDC supply; connection: 5 pin m12 male a-coded. Choose colour, lens / beam angle below (20 configurations) and request a quote. Rendered illustration: the actual product may differ in appearance.



Common specifications

Lit width (mm)	21.8
Width (mm)	148.4
Height (mm)	62.6
Voltage	24 VDC
Connector	5 Pin M12 Male A-Coded
Connection at light	Connectorized
Driver included	Included
Driver location	Internal
Operating modes	Constant On
Strobe trigger input	Constant On Only
Operating temperature	10 to 40 °C
IP rating	IP50
Housing	Aluminum
Mounting	T-Slot Channels
Collimated	Not Collimated
Daisy chain	No
Diffused	Not Diffused
Maximum duty cycle (%)	100
Polarized	Not Polarized
Storage temperature	20 to 70 °C
Compliance	CE, IEC 62471, RoHS

Models

Model	Lit length (mm)	Length (mm)	Direct connect	Maximum constant on current (ma)	Maximum input power constant on (w)
LS-LSC-0020	1196	1209	No	6400	153.6
LS-LSC-0021	296	309.1	No	1600	38.4
LS-LSC-0022	596	609.1	Yes	3200	76.8
LS-LSC-0023	896	909.1	No	4800	115.2

Product views

