

Classic line lights

LS-LTDS-C series · Line scan lights · 10 models

One-piece aluminum alloy housing for good heat dissipation
Added diffuser film for good uniformity

Features

- One-piece aluminum alloy housing for good heat dissipation
- Added diffuser film for good uniformity
- Nut slots on top and bottom for flexible mounting



Common specifications

Color	White
Color temperature	6000-7000K
Connector type	20M-4J
LED rows	1
Cable length	500 mm
Temperature	Working temperature: 0 °C to 40 °C (32 °F to 104 °F); Storage temperature: -20 °C to 60 °C (-4 °F to 140 °F)
Humidity	20% to 85% RH (non-condensing)
Diffuse plate included	Included

Models

Model	Power	Dimension	Emitting area dimension
LS-LTDS-150-W	23.0 W	188 mm × 45 mm × 71 mm	150 mm × 17 mm
LS-LTDS-300-W	46.1 W	338 mm × 45 mm × 49.8 mm	300 mm × 17 mm
LS-LTDS-450-W	69.1 W	488 mm × 45 mm × 71 mm	450 mm × 17 mm
LS-LTDS-600-W	92.2 W	638 mm × 45 mm × 49.8 mm	600 mm × 17 mm
LS-LTDS-750-W	115.2 W	788 mm × 45 mm × 71 mm	750 mm × 17 mm
LS-LTDS-750-DW	115.2 W	788 mm × 45 mm × 71 mm	750 mm × 17 mm
LS-LTDS-1200-W	184.3 W	1256 mm × 45 mm × 71 mm	1200 mm × 17 mm
LS-LTDS-1350-W	207.4 W	1406 mm × 45 mm × 49.8 mm	1350 mm × 17 mm
LS-LTDS-1500-W	230.4 W	1556 mm × 45 mm × 49.8 mm	1500 mm × 17 mm
LS-LTDS-1800-W	276.5 W	1856 mm × 45 mm × 49.8 mm	1800 mm × 17 mm

Performance

