

Ring light

LS-RNG-0004 series · Ring lights · 1 model

Ring light.
Connection:
Flying Leads.
Available in
576
configurations
(active
diameter
(mm), color,
driver
included,
driver
location);
choose one
below and
request a
quote.
Rendered
illustration:
the actual
product may
differ in
appearance.



Options

Active Diameter (mm)	95.3, 145.3, 206.9, 246.9
Color	365nm Ultraviolet (UV), 375nm Ultraviolet (UV), 385nm Ultraviolet (UV), 395nm Ultraviolet (UV), 405nm Violet, 455nm Blue, 470nm Blue, 505nm Cyan, 530nm Green, 590nm Amber, 625nm Red, 660nm Red, 730nm Infrared, 850nm Infrared, 940nm Infrared, WHITE
Driver Included	No Driver Required, Included
Driver Location	No Driver, In Line
Driver Nomenclature	24V, iCS2 - IC, iCS4 - I4
Height (mm)	33.1, 31.1, 31.9
Inner Diameter (mm)	50, 100, 160, 200
Lens Angle	32 Degree, 20 Degree
Maximum Constant On Current (mA)	140, 470, 270, 790, 980, 540, 400
Maximum Input Power Constant On (W)	3.4, 11.3, 6.5, 19, 23.5, 13, 9.6
Maximum Input Power Overcurrent Strobe (W)	125, 150
Maximum Overcurrent Strobe Latency (us)	60, 20
Operation Modes	Constant On, Constant On, Constant On - Dimmable, Overcurrent Strobe, Overcurrent Strobe - Dimmable, Constant On, Constant On - Dimmable
Outer Diameter (mm)	95.3, 145.3, 206.9, 246.9
Product Weight (Kg)	0.3, 0.4, 0.54, 0.64
Product Weight (Lbs)	0.66, 0.88, 1.18, 1.42
Strobe Trigger Input	Constant On Only, PNP Trigger


