

# Ring light, 140 mm

LS-RNG-0049 series · Ring lights · 1 model

LED ring light that mounts around the lens for even, on-axis illumination of the field of view. 24 VDC supply; connection: 5 pin m12 male a-coded. Choose colour, lens / beam angle below (32 configurations) and request a quote. Rendered illustration: the actual product may differ in appearance.



## Options

|                   |                                                                                                                                       |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Colour            | 365nm Ultraviolet (UV), 395nm Ultraviolet (UV), 470nm Blue, 505nm Cyan, 530nm Green, 625nm Red, 850nm Infrared, 940nm Infrared, WHITE |
| Lens / beam angle | 10 Degree, 25 Degree, 50 Degree, 30 Degree, 80 Degree                                                                                 |

Order by the full LS number of the chosen configuration; we confirm it with your quote.

## Common specifications

|                        |                                                                                                                   |
|------------------------|-------------------------------------------------------------------------------------------------------------------|
| Lit diameter (mm)      | 126.7                                                                                                             |
| Height (mm)            | 41                                                                                                                |
| Outer diameter (mm)    | 140                                                                                                               |
| Inner diameter (mm)    | 67.7                                                                                                              |
| Viewport diameter (mm) | 67.7                                                                                                              |
| Voltage                | 24 VDC                                                                                                            |
| Connector              | 5 Pin M12 Male A-Coded                                                                                            |
| Connection at light    | Connectorized                                                                                                     |
| Cable length (mm)      | 254                                                                                                               |
| Driver included        | Included                                                                                                          |
| Driver location        | Internal                                                                                                          |
| Intensity control      | Analog Voltage                                                                                                    |
| Operating modes        | Constant On, Constant On – Dimmable, Overcurrent Strobe, Overcurrent Strobe – Dimmable, Strobe, Strobe – Dimmable |
| Strobe trigger input   | NPN Trigger, PNP Trigger                                                                                          |

## Models

Model

LS-RNG-0049

## Product views

