

Ring light, 95.3–246.9 mm

LS-RNG-0004 series · Ring lights · 1 model

LED ring light that mounts around the lens for even, on-axis illumination of the field of view. 24 VDC supply; connection: flying leads. Choose colour, lens / beam angle, outer diameter, lit diameter, driver included below (576 configurations) and request a quote. Rendered illustration: the actual product may differ in appearance.



Options

Colour	365nm Ultraviolet (UV), 375nm Ultraviolet (UV), 385nm Ultraviolet (UV), 395nm Ultraviolet (UV), 405nm Violet, 455nm Blue, 470nm Blue, 505nm Cyan, 530nm Green, 590nm Amber, 625nm Red, 660nm Red, 730nm Infrared, 850nm Infrared, 940nm Infrared, WHITE
Lens / beam angle	32 Degree, 20 Degree
Outer diameter (mm)	95.3, 145.3, 206.9, 246.9
Lit diameter (mm)	95.3, 145.3, 206.9, 246.9
Driver included	No Driver Required, Included
Driver location	No Driver, In Line
Intensity control	Not listed, Analog Voltage
Operating modes	Constant On, Constant On, Constant On – Dimmable, Overcurrent Strobe, Overcurrent Strobe – Dimmable, Constant On, Constant On – Dimmable
Strobe trigger input	Constant On Only, PNP Trigger
Minimum overcurrent strobe duration (us)	Not listed, 30
Version	Standard, Version 1, Version 2

Order by the full LS number of the chosen configuration; we confirm it with your quote.

Common specifications

Height (mm)	31.1 / 31.9 / 33.1 (by configuration)
Inner diameter (mm)	50 to 200 (by configuration)
Viewport diameter (mm)	50 to 200 (by configuration)
Voltage	24 VDC
Connector	Flying Leads
Connection at light	Hardwired
Cable length (mm)	2000
Operating temperature	up to 60 °C
IP rating	IP50
Housing	Aluminum
Mounting	Tapped Holes
Collimated	Not Collimated
Daisy chain	No
Diffused	Not Diffused
Direct connect	No
Maximum constant on current (ma)	140 to 980 (by configuration)
Maximum current (overcurrent strobe) (ma)	8000 (by configuration)
Maximum duty cycle (%)	100
Maximum input power constant on (w)	3.4 to 23.5 (by configuration)
Maximum input power overcurrent strobe (w)	125 / 150 (by configuration)
Maximum overcurrent strobe frequency (hz)	2000 (by configuration)
Maximum overcurrent strobe latency (us)	20 / 60 (by configuration)
NPN trigger voltage (v)	< 1 VDC (by configuration)
PNP trigger current (ma)	5 (by configuration)
PNP trigger voltage (v)	2.5-30 VDC (by configuration)
Polarized	Not Polarized
Compliance	CE, IEC 62471, RoHS

Models

Model

LS-RNG-0004

Product views

