


243 x 243 mm spot light

LS-SPT-0104 series · Spot lights · 1 model

243 x 243 mm spot light. Lit area 153 x 153 mm.
 Connection: 5 Pin M12 Male A-Coded.
 Available in 7 configurations (color); choose one below and request a quote.
 Rendered illustration: the actual product may differ in appearance.



Options

Color 470nm Blue, 505nm Cyan, 530nm Green, 625nm Red, 850nm Infrared, 940nm Infrared, WHITE

Order by the full LS number of the chosen configuration; we confirm it with your quote.

Common specifications

Active Length (mm)	153
Active Width (mm)	153
Collimated	Not Collimated
Compliances	CE, IEC 62471, RoHS
Connector Type	5 Pin M12 Male A-Coded
Connectorized At Light	Connectorized
Daisy Chain	No
Direct Connect	No
Driver Included	Included
Driver Location	Internal
Driver Nomenclature	SVL Smart Driver
Height (mm)	93.5
Housing Material	Aluminum
IP Rating	IP50
Intensity Adjustment Type	Analog Voltage
Length (mm)	243
Lens Angle	Diffused
Maximum Constant On Current (mA)	820

Maximum Duty Cycle (%)	100
Maximum Input Power Constant On (W)	19.7
Maximum Operating Temperature (C)	50
Maximum Operating Temperature (F)	122
Maximum Storage Temperature (C)	50
Maximum Storage Temperature (F)	122
Minimum Operating Temperature (C)	-20
Minimum Operating Temperature (F)	-4
Minimum Storage Temperature (C)	-20
Minimum Storage Temperature (F)	-4
Mounting Method	T-Slot Channels
NPN Trigger Current (mA)	22
NPN Trigger Voltage (V)	< 1 VDC
Operation Modes	Constant On, Constant On – Dimmable
PNP Trigger Current (mA)	30.4
PNP Trigger Voltage (V)	3.3-24 VDC
Polarized	Not Polarized
Product Weight (Kg)	2.22
Product Weight (Lbs)	4.9
Strobe Trigger Input	NPN Trigger, PNP Trigger
Voltage	24 VDC
Width (mm)	243

Models

Model

LS-SPT-0104

Product views

