


Spot light, 46 x 69 mm lit area

LS-SPT-0118 series · Spot lights · 1 model

Compact spot light for small fields of view and high intensity at a distance. Lit area 46 x 69 mm; 24 VDC supply; connection: 5 pin m12 male a-coded. Choose colour below (7 configurations) and request a quote. Rendered illustration: the actual product may differ in appearance.



Options

Colour 470nm Blue, 505nm Cyan, 530nm Green, 625nm Red, 850nm Infrared, 940nm Infrared, WHITE

Order by the full LS number of the chosen configuration; we confirm it with your quote.

Common specifications

Lens / beam angle	Diffused
Lit length (mm)	46
Lit width (mm)	69
Length (mm)	69
Width (mm)	77
Height (mm)	35.7
Voltage	24 VDC
Connector	5 Pin M12 Male A-Coded
Connection at light	Connectorized
Driver included	Included
Driver location	Internal
Intensity control	Analog Voltage, Integrated Potentiometer
Operating modes	Constant On, Constant On – Dimmable
Strobe trigger input	NPN Trigger, PNP Trigger
Operating temperature	-18 to 40 °C
IP rating	IP50
Housing	Plastic

Mounting	Through Holes
Collimated	Not Collimated
Daisy chain	No
Diffused	Diffused
Direct connect	No
Driver nomenclature	SVL Smart Driver
Maximum constant on current (ma)	375
Maximum duty cycle (%)	100
Maximum input power constant on (w)	9
NPN trigger current (ma)	15
NPN trigger voltage (v)	< 1 VDC
PNP trigger current (ma)	20
PNP trigger voltage (v)	4-24 VDC
Polarized	Not Polarized
Storage temperature	-18 to 40 °C
Compliance	CE, IEC 62471, RoHS

Models

Model
LS-SPT-0118

Product views

