

Side back light source (2FS)

LS-2FS series · Backlights · 13 models

Ultra-thin side (edge-lit) backlight; light from several sides gives overall uniformity and the thin design fits tight installation spaces. Flexible sizes and convenient customization.



Features

- Multilateral lights make the overall uniformity
- Ultra-thin design, can meet different installation space requirements
- Flexible size, convenient customization, wide range of applications
- Various installation methods for convenient mounting

Applications

- Liquid level inspection
- Dimension measurement
- Liquid foreign matter inspection
- Burr inspection for metal profile
- Appearance inspection
- Dimension measuring for workpiece
- Inspection for surface scratches of transparent objects and internal foreign matter
- Film stain inspection

Colours

R	620-630 nm
G	520-530 nm
B	465-475 nm
W	6000-6500 K

Common specifications

Wavelength red	620-630 nm
Wavelength green	520-530 nm
Wavelength blue	465-475 nm
Colour temperature white	6000-6500 K
Wavelength IR	850-940 nm
Wavelength UV	365-405 nm

Storage temperature	20 to 60 °C
Operating temperature	0 to 40 °C
Humidity	20-85 %RH (non-condensing)
Optional accessories	Extension cable
Controller	LS-DPS series, LS-APS series, LS-SPS series (the selected controller should match the power of the light source)
Service life (red)	60000 h continuous at 25 °C, 50% illumination, to 50% decrement
Service life (white)	30000 h continuous at 25 °C, 50% illumination, to 50% decrement
Warranty	1 year from shipment (faults not caused by the user: free repair or replacement)
Illuminance chart reference	LS-2FS100100-W; uniformity at LWD 100 mm, FOV 140 x 140 mm

Ordering code: LS-2FS<luminous length mm><luminous width mm>-<R/G/B/W> (2 = version, FS = side back light source)

Models


Model	Power R (W)	Power G/B/W (W)	Luminous size (mm)	Overall L (mm)	Overall W (mm)	Overall H (mm)
LS-2FS5050-R/G/B/W colours: R, G, B, W	5.6	9	50 x 50	82	82	10.5
LS-2FS100100-R/G/B/W colours: R, G, B, W	12	14	100 x 100	132	132	10.5
LS-2FS150150-R/G/B/W colours: R, G, B, W	17	18	150 x 150	182	182	10.5
LS-2FS200150-R/G/B/W colours: R, G, B, W	23	23	200 x 150	232	182	10.5
LS-2FS200200-R/G/B/W colours: R, G, B, W	23	23	200 x 200	232	232	10.5
LS-2FL250200-R/G/B/W colours: R, G, B, W	28	27	250 x 200	282	232	10.5
LS-2FS268168-R/G/B/W colours: R, G, B, W	28	32	268 x 168	300	200	10.5
LS-2FS300200-R/G/B/W colours: R, G, B, W	28	32	300 x 200	332	232	10.5
LS-2FS320320-R/G/B/W colours: R, G, B, W	34	36	320 x 320	352	352	10.5
LS-2FS400300-R/G/B/W colours: R, G, B, W	54	56	400 x 300	432	332	10.5
LS-2FS450350-R/G/B/W colours: R, G, B, W	49	56	450 x 350	482	382	10.5
LS-2FS568568-R/G/B/W colours: R, G, B, W	56	79	568 x 568	600	600	12.5
LS-2FS600400-R/G/B/W colours: R, G, B, W	68	79	600 x 400	632	432	11.5

More values per model (Recommended controller) are on each product page.

Dimensions


LS-2FS5050

1




LS-2FS100100

2




LS-2FS150150

3




LS-2FS200150

4




LS-2FS200200

5




LS-2FS250200

6




LS-2FS268168

7




LS-2FS300200

8




LS-2FS320320

9




LS-2FS400300

10




LS-2FS450350

11




LS-HFS568568

12






LS-2FS600400

13



Performance



Product views

