

360 degree industrial lens (LS-OR / LS-IR)

LS-360-H series · 360° inspection lenses · 10 models

360 degree Industrial lens is divided into internal and external observations. It detects the internal view or appearance of the measured object in 360 degrees, and transmits HD images in real time.



Features

- Sensor Size: 1/1.8".
- Working Distance: 9-45.4mm.
- F/NO: F8-16, C-Mount.
- High contrast and excellent imaging effects.
- Suitable for appearance detection, inner wall detection, cylinder and complex structure detection, etc.

Models

Model	Sensor Size	Working distance(mm)	Target Dia(mm)	Inspection Height(mm)	Type	WD	Sensor format
LS-OR3601802A	1/1.8"	9-45.4	7.5-30	5.3-25	360 Degree Industrial Lens-Outer Wall Detection	9-45.4mm	1/1.8"
LS-OR3602303A	2/3"	15-49	7.5-30	4.2-23.5	360 Degree Industrial Lens-Outer Wall Detection	15-49mm	2/3"
LS-OR3601204A	1/2"	8-44	7-35	5-28	360 Degree Industrial Lens-Outer Wall Detection	8-44mm	1/2"

LS-OR3601305A	1/3"	9.7-46.5	7.5-30	6.4-25.6	360 Degree Industrial Lens-Outer Wall Detection	9.7-46.5mm	1/3"
LS-IR3602306A	2/3"	2.7-70	5-120	5-123	360 Degree Industrial Lens-Inner Wall Detection	2.7-70mm	2/3"
LS-IR3601306A	1/3"	12.5-50	25-100	12.4-58.2	360 degree Viewing lens	12.5-50mm	1/3"
LS-OR3601207A	1/2"	10-43	30-80	26.5-46.6	360 Degree Industrial Lens-Outer Wall Detection	10-43mm	1/2"
LS-OR3602308A	2/3"	2-5	0.8-30	7.6-17	360 Degree Industrial Lens-Octagonal mirror	2-5mm	2/3"
LS-OIR3601809A	2/3"	12.6	5-70	7.1-26.6	360 Degree Industrial Lens-Octagonal mirror	12.6mm	2/3"
LS-OR3601811A	1/2"	15-66	5-40	5-10	360 Degree Industrial Lens-Outer Wall Detection	15-66mm	1/2"

More values per model (F/NO., Image Size(mm), Mount, Image Size, Target Dia, Inspection Height, Mount (product page), Main Material, Color, Weight (g), Warranty, Custom Design...) are on each product page.

Dimensions

[illegible]

Address: 6A, 168 Smart buildings, Heng Gang Tou industrial park of Xin'an community, Chang An Town, Dong Guan, China.

Product views

