

Analog point light controller, 2 channels (AC65)

LS-AC-2CH series · Light controllers · 1 model



Analog constant current control. Support external trigger mode. Low trigger response time.

Features

- Analog constant current control
- Support external trigger mode
- Low trigger response time
- Knob stepless linear adjustment of brightness
- Normally bright and normally off mode can be switched
- 5-24V trigger, adaptable to high and low level trigger modes
- Convenient installation, screw mounting or C45 rail mounting

Common specifications

Maximum output current of single channel	0.75A
Maximum input voltage	220VAC
Maximum output voltage	5V
Overheat protection	YES
Working mode	Constant on mode, constant off mode
Short circuit protection	NO
Brightness level	Knob stepless linear adjustment
Trigger mode	Level Trigger
Operating temperature	5~50°C
Connected light source type (parameter table)	5V point light source
Luminous mode	Constant Brightness
Number of channels (parameter table)	Two channels
Built-in power supply	65W
Driving mode	Constant Current
Dimension	121x118x90mm

Ordering code: LS-AC<built-in power supply W>-<max output voltage><max output current of single channel>-<number of channels> (AC = analog constant current type), e.g. LS-AC65-050075-2

Models

Model	Built-in power supply power	Number of channels	Connected light source type	Catalog page	Total output (W)	Control
LS-AC65-050075-2	65W	2	5V point light source	P52	65	analog knob

Dimensions

