

Digital point light controller, 4 channels (DC-P03C)

LS-DC-P03C series · Light controllers · 1 model

Support RS232 communication. Support 100Gb Ethernet communication. Built-in 5V switching power supply.

Features

- Support RS232 communication
- Support 100Gb Ethernet communication
- Built-in 5V switching power supply
- Low trigger response time
- Support external trigger mode
- Normal light / strobe can be switched
- Support millisecond strobe and microsecond strobe
- Brightness and mode can be set manually
- 5~24V trigger, adaptable to high and low level trigger modes
- Easy to install, screw mounting or C45 rail mounting



Common specifications

Single channel instantaneous maximum current	2A
Maximum input voltage	AC220V
Maximum output voltage	5V
Overheat protection	NO
Working mode	NOR: constant light (printed in pinyin 'Hengliang'); TRIG: 0: Constant off 1.1-999 milliseconds flicker (as printed)
Short circuit protection	NO
Brightness level	255 levels
Connection light source type	5V point light source
Millisecond strobe time	1~999ms
Communication	9600~115200bps optional
Trigger mode	Edge + level trigger
Operating temperature	5~50°C
Luminous mode	Normal light, normal extinction, constant Brightness, strobe
Number of channels	4
Dimension	89×147×175mm

Ordering code: LS-DC<built-in power supply W>-P 03 C-<max output voltage><max output current of single channel>-<number of channels> (DC = digital current type, P = spot light, 03 = 03 series, C = supports RS232), e.g. LS-DC65-P03C-05020-4

Models

Model	Built-in power supply power	Connected light source type	Catalog page	Total output (W)	Control
LS-DC65-P03C-05020-4	65W	5V point light source	P48	65	digital (buttons, 4-digit display) / RS232 (features also list 100Gb Ethernet)

Dimensions

