

Dust proof controller (IP)

LS-IP-CTRL series · Light controllers · 4 models

Has developed IP series dustproof controller according to customer demand, and the dustproof level of this controller has reached IP54 level, providing customers with more applications, ensuring product stability and prolonging life.



Features

- IP5X dustproof protection, suitable for dusty environments
- Luminance adjustable
- LAN and RS232 port
- With external trigger function
- Good heat dissipation

Common specifications

Input voltage	AC 100-240V
Dust proof level	Level 5 (IP5X)
Operating environment	Humidity 20%-85%RH (non-condensing), temperature 0°C-50°C
Storage environment	Humidity 20%-85%RH (non-condensing), temperature 0°C-50°C
Output voltage	24V
Product	Dust Proof Controller

Models

Model	Total output power	One way Max.output power	Number of channels	Remark	Drive mode	Luminance adjustment method	Luminance adjustment level
-------	--------------------	--------------------------	--------------------	--------	------------	-----------------------------	----------------------------

LS-3DPC24120-8S-IP	120W	60W	8	Communication, external trigger, luminance level, display and etc.	PWM driving	Manual encoder knob adjustment, PC remote adjustment	256 level
LS-3DPC24200-8S-IP	200W	60W	8	Communication, external trigger, luminance level, display and etc.	PWM driving	Manual encoder knob adjustment, PC remote adjustment	256 level
LS-APC24240-1-IP	240W	240W	1	-	Constant driving	Manual stepless adjustment	Stepless
LS-APC24480-1-IP	480W	480W	1	-	Constant driving	Manual stepless adjustment	Stepless

More values per model (Communication mode, Baud rate, Power input frequency range, Trigger voltage, Memory function, External trigger frequency, External trigger response time) are on each product page.