

USB2.0 area scan camera (U2 series)

LS-MV-U2 series · Area scan cameras · 4 models

This series of USB2.0 area scan cameras includes color and monochrome, global and rolling shutter. Extremely cost-effective, ultra-low power consumption.

Features

- Support a single PC multiple cameras at the same time stable work.
- Stable and reliable, suitable for vibration applications.
- Supports Windows XP SP3 and above, as well as Linux 32-bit/64-bit operating systems.
- Dimensions: 29mm×29mm×29mm.



Models

Model	Target size	Resolution	Pixel size	Shutter	Frame rate	Color/Mono	Mono / colour
LS-MV-132U2C/M30-GS	1/2.7"	1280*1024	4.0um	Global	30FPS	Color/Mono	Color/Mono
LS-MV-138U2M30-GS	1/2"	1280*1024	4.8um	Global	30FPS	Mono	Mono
LS-MV-500U2C8-RS-M2	1/2.5"	2592*1944	2.2um	Rolling	7.9FPS	Color	Color
LS-MV-500U2C/M8-RS	1/2.5"	2592*1944	2.2um	Rolling	7.9FPS	Color/Mono	Color/Mono

More values per model (Data interface, Lens Mount, Sensor Type, Resolution (product page), Optical Size, Mono/Color, Max Frame Rate, Gain, Dynamic range, Exposure Time, Sensitivity, Output Image Format...) are on each product page.